



- NOTES:**
1. PIN 1 INDICATED BY SQUARE PAD
 2. UNDIMENSIONED HOLES ARE ON 0.100 CENTERS FROM DIMENSIONED HOLE ON EACH CONNECTOR.
 3. MOUNTING HOLES ALL HAVE DIAMETER 0.116 WITH CENTER PLACED 0.25 FROM EACH BOARD EDGE.

* Overhang = 0.07 TYP
 + Overhang = 0.09 TYP

THIS DOCUMENT IS PROTECTED BY US AND OTHER COPYRIGHT LAW AND IS THE SOLE PROPERTY OF JK microsystems AND IS TO BE USED ONLY FOR INFORMATION IN THE USE OR MANUFACTURE OF JK microsystems PRODUCTS

			TOLERANCES UNLESS OTHERWISE SPECIFIED DIMENSIONS IN INCHES X.XX ± 0.02 X.XXX ± 0.010 X.XXXX ± 0.0050 DO NOT SCALE DRAWING	DRAWN: AY SCALE: NONE DATE: 03 / 01 / 06	TITLE: CONNECTOR DRAWING OMNIFLASH			
					MODEL	JK microsystems	SIZE B	DWG NO.
1	First Issue	3/1/06						
REV	REVISION RECORD	DATE		REMOVE ALL BURS	FILE: Omni_mech.pdf	California, USA http://www.jkmicro.com		